Claims:

1. An apparatus adapted to disseminate volatile liquid into an atmosphere, comprising:

a stationary support an electromagnet equipped with a power source, an electromagnet control means and at least one stationary support arm extending from the stationary support;

an oscillating portion having at least one pivot arm extending therefrom pivotally mounted upon the at least one stationary support arm, a permanent magnet at or near the lowest region of the oscillating portion, a reservoir containing a liquid air treatment material in fluid communication with an evaporating surface;

wherein the operation of the electromagnet control means maintains oscillatory motion of the oscillating portion with respect to the stationary support and dissemination of the air treatment material to the atmosphere.

2. An apparatus according to claim 1 wherein the oscillating portion includes a body portion.

3. An apparatus according to claim 1 wherein the oscillating portion is a body portion.

4. An apparatus according to claim 1 wherein the electromagnet control includes a timer or timer circuit.

5. An apparatus according to claim 1 wherein the electromagnet control means is a power control circuit.

6. An apparatus according to claim 1 wherein the electromagnetic control means is a switch circuit.

7. An apparatus according to claim 1 which comprises a primary wick and a secondary wick.

8. A method of disseminating a volatile liquid into an atmosphere, comprising the steps of providing an apparatus according to claim 1, operating the device and thereby causing the

oscillation of the oscillating portion of the device, the oscillation being maintained by means of a pair of magnets of the device, to cause an evaporation surface that is supplied with liquid to oscillate in the atmosphere.

5